

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Power Cable

Cu/PVC/PVC 0.6/1 kV (NYY)



Specification :
SNI IEC 60502-1 : 2009

Constructions:

Conductor

Annealed plain copper round solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :
- Light Blue



Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride PVC Grade ST1 to SNI IEC 60502-1. Black Colour

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

• Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
• UV Resistance • Anti termite • Anti rodent • Low Smoke Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor

Packing : D] Drum

No. of cores and cross section area	Nominal thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity @ 30°C				Short Circuit Current Capacity @ 1.0 sec	Standard Delivery Length
	Insulation	Outer Sheath				In Air		In Ground			
											
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	A	A	kA	m
1 x 1.5 re	0.8	1.4	5.8	50	12	21	27	27	27	0.17	1000/D
1 x 1.5 rm	0.8	1.4	6	52	11	21	24	27	27	0.17	1000/D
1 x 2.5 re	0.8	1.4	6.2	63	10	28	27	35	35	0.29	1000/D
1 x 2.5 rm	0.8	1.4	6.5	67	9	28	27	35	35	0.29	1000/D
1 x 4 re	1.0	1.4	7.1	87	10	38	37	45	46	0.46	1000/D
1 x 4 rm	1.0	1.4	7.4	92	9	38	37	45	46	0.46	1000/D
1 x 6 re	1.0	1.4	7.6	110	9	48	46	57	57	0.69	1000/D
1 x 6 rm	1.0	1.4	8	117	8	48	46	57	57	0.69	1000/D
1 x 10 re	1.0	1.4	8.5	157	7	65	64	76	76	1.15	1000/D
1 x 10 rm	1.0	1.4	8.8	163	6	65	64	76	76	1.15	1000/D
1 x 16 rm	1.0	1.4	10	227	5	87	84	97	98	1.84	1000/D
1 x 25 rm	1.2	1.4	11.6	336	5	117	114	125	127	2.88	1000/D
1 x 35 rm	1.2	1.4	12.7	437	4	144	140	150	152	4.03	1000/D
1 x 50 rm	1.4	1.4	14.3	562	4	177	172	178	180	5.75	1000/D
1 x 70 rm	1.4	1.4	16	768	4	225	218	218	220	8.05	1000/D
1 x 95 rm	1.6	1.5	18.5	1049	4	278	270	260	264	10.93	1000/D
1 x 120 rm	1.6	1.5	20	1280	3	325	315	296	300	13.8	1000/D
1 x 150 rm	1.8	1.6	22.5	1275	3	373	362	331	336	17.25	1000/D
1 x 185 rm	2.0	1.7	24.5	1959	3	433	420	374	379	21.28	1000/D
1 x 240 rm	2.2	1.8	28	2538	3	518	503	432	439	27.6	1000/D
1 x 300 rm	2.4	1.9	31	3157	3	598	580	486	494	34.5	1000/D
1 x 400 rm	2.6	2.0	34	3995	3	695	674	549	558	46	1000/D
1 x 500 rm	2.8	2.1	38	5075	3	806	781	618	629	57.5	1000/D
1 x 630 rm	2.8	2.3	43	6449	3	930	901	692	704	72.45	500/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Power Cable

Cu/PVC/PVC 0.6/1 kV (NYY)

Specification :
SNI IEC 60502-1 : 2009



Constructions:

Conductor

Annealed plain copper round solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1 Colour

Colour :

- Light Blue, Brown



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

- Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
- UV Resistance • Anti termite • Anti rodent • Low Smoke
- Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor

Packing : [D] Drum

No. of cores and cross section area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
2 x 1.5 re	0.8	1.8	10.8	159	12	27	21	0.17	1000/D
2 x 1.5 rm	0.8	1.8	11.1	168	11	27	21	0.17	1000/D
2 x 2.5 re	0.8	1.8	11.6	196	10	36	29	0.29	1000/D
2 x 2.5 rm	0.8	1.8	12.1	209	9	36	29	0.29	1000/D
2 x 4 re	1.0	1.8	13.3	269	10	47	38	0.46	1000/D
2 x 4 rm	1.0	1.8	13.9	289	9	47	38	0.46	1000/D
2 x 6 re	1.0	1.8	14.3	333	9	59	48	0.69	1000/D
2 x 6 rm	1.0	1.8	15.1	359	8	59	48	0.69	1000/D
2 x 10re	1.0	1.8	16.1	452	7	78	66	1.15	1000/D
2 x 10 rm	1.0	1.8	16.8	485	6	78	66	1.15	1000/D
2 x 16 rm	1.0	1.8	18.9	657	5	102	90	1.84	1000/D
2 x 25 rm	1.2	1.8	22.3	959	5	134	120	2.88	1000/D
2 x 35 rm	1.2	1.8	24.5	1224	4	160	150	4.03	1000/D
2 x 50 rm	1.4	1.8	27.7	4578	4	187	180	5.75	1000/D
2 x 70 rm	1.4	1.9	31.4	2131	4	230	230	8.05	1000/D
2 x 95 rm	1.6	2	36.4	2905	4	280	275	10.93	1000/D
2 x 120 rm	1.6	2.1	39.7	3531	3	320	320	13.80	1000/D
2 x 150 rm	1.8	2.2	43.7	4321	3	355	379	17.25	500/D
2 x 185 rm	2.0	2.4	48.6	5368	3	409	430	21.28	500/D
2 x 240 rm	2.2	2.6	55.1	6964	3	472	510	27.60	500/D
2 x 300 rm	2.4	2.7	60.8	8605	3	525	590	34.50	500/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Power Cable

Cu/PVC/PVC 0.6/1 kV(NYY)



Specification :
SNI IEC 60502-1 : 2009

Constructions:

Conductor

Annealed plain copper round solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :

- Yellow Strip Green, Light Blue and Brown
- Brown, Black And Grey



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

• Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
• UV Resistance • Anti termite • Anti rodent • Low Smoke
Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor
[Sm] Sector shape conductor

Packing : [D] Drum

No. of cores and cross section area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
3 x 1.5 re	0.8	1.8	11.2	181	12	24	18	0.17	1000/D
3 x 1.5 rm	0.8	1.8	11.6	191	11	24	18	0.17	1000/D
3 x 2.5 re	0.8	1.8	12.1	229	10	32	25	0.29	1000/D
3 x 2.5 rm	0.8	1.8	12.6	245	9	32	25	0.29	1000/D
3 x 4 re	1.0	1.8	14	319	10	41	34	0.46	1000/D
3 x 4 rm	1.0	1.8	14.6	342	9	41	34	0.46	1000/D
3 x 6 re	1.0	1.8	15.1	401	9	52	44	0.69	1000/D
3 x 6 rm	1.0	1.8	15.9	433	8	52	44	0.69	1000/D
3 x 10 re	1.0	1.8	17.1	578	7	69	60	1.15	1000/D
3 x 10 rm	1.0	1.8	17.8	596	6	69	60	1.15	1000/D
3 x 16 rm	1.0	1.8	20	822	5	89	80	1.84	1000/D
3 x 25 rm	1.2	1.8	23.6	1213	5	116	105	2.88	1000/D
3 x 35 rm	1.2	1.8	26	1565	4	138	130	4.03	1000/D
3 x 50 sm	1.4	1.8	25.3	1898	4	165	160	5.75	1000/D
3 x 70 sm	1.4	2	28.6	2580	4	205	200	8.05	1000/D
3 x 95 sm	1.6	2.1	32.7	3485	4	245	245	10.93	1000/D
3 x 120 sm	1.6	2.2	35.5	4312	3	285	285	13.80	1000/D
3 x 150 sm	1.8	2.3	39.2	5300	3	315	325	17.25	500/0
3 x 185 sm	2.0	2.5	43.8	6478	3	355	370	21.28	500/D
3 x 240 sm	2.2	2.7	49.3	8491	3	415	435	27.60	500/D
3 x 300 sm	2.4	3.1	55	10652	3	535	600	34.50	500/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Power Cable

Cu/PVC/PVC 0.6/1 kV (NYY)

Specification :
SNI IEC 60502-1 : 2009



Constructions:

Conductor

Annealed plain copper round solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :

- Yellow Strip Green, Brown, Black and Grey
- Light Blue, Brown, Black And Grey



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

- Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
- UV Resistance • Anti termite • Anti rodent • Low Smoke Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor
[Sm] Sector shape conductor

Packing : [D] Drum

No. of Cores and Cross Section Area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
4 x 1.5 re	0.8	1.8	12	213	12	24	18	0.17	1000/D
4 x 1.5 rm	0.8	1.8	12.4	224	11	24	18	0.17	1000/D
4 x 2.5 re	0.8	1.8	13	273	10	32	25	0.29	1000/D
4 x 2.5 rm	0.8	1.8	13.6	292	9	32	25	0.29	1000/D
4 x 4 re	1.0	1.8	15.1	385	10	41	34	0.46	1000/D
4 x 4 rm	1.0	1.8	15.8	413	9	41	34	0.46	1000/D
4 x 6 re	1.0	1.8	16.3	490	9	52	44	0.69	1000/D
4 x 6 rm	1.0	1.8	17.2	527	8	52	44	0.69	1000/D
4 x 10 re	1.0	1.8	20.3	724	7	69	60	1.15	1000/D
4 x 10 rm	1.0	1.8	21	743	6	69	60	1.15	1000/D
4 x 16 rm	1.0	1.8	24	1035	5	89	80	1.84	1000/D
4 x 25 rm	1.2	1.8	28	1541	5	116	105	2.88	1000/D
4 x 35 rm	1.2	1.8	30	1999	4	138	130	4.03	1000/D
4 x 50 sm	1.4	1.9	32	2498	4	165	160	5.75	1000/D
4 x 70 sm	1.4	2.1	36	3374	4	205	200	8.05	1000/D
4 x 95 sm	1.6	2.2	40	4536	4	245	245	10.93	1000/D
4 x 120 sm	1.6	2.3	44	5676	3	285	285	13.80	1000/D
4 x 150 sm	1.8	2.5	49	6910	3	315	325	17.25	500/D
4 x 185 sm	2.0	2.7	53	8596	3	355	370	21.28	500/D
4 x 240 sm	2.2	2.9	60	11087	3	415	435	27.60	500/D
4 x 300 sm	2.4	3.1	66	13549	3	465	500	34.50	500/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Power Cable

Cu/PVC/PVC 0.6/1 kV (NYY)



Specification :
SNI IEC 60502-1 : 2009

Constructions:

Conductor

Annealed plain copper solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :

- Yellow Strip Green, Light Blue, Brown, Black and Grey



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

- Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
- UV Resistance • Anti termite • Anti rodent • Low Smoke Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor

Packing : [D] Drum

No. of Cores and Cross Section Area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
5 x 1.5 re	0.8	1.8	12.8	255	12	24	18	0.17	1000/D
5 x 1.5 rm	0.8	1.8	13.3	268	11	24	18	0.17	1000/D
5 x 2.5 re	0.8	1.8	14	329	10	32	25	0.29	1000/D
5 x 2.5 rm	0.8	1.8	14.6	352	9	32	25	0.29	1000/D
5 x 4 re	1.0	1.8	16.3	470	10	41	34	0.46	1000/D
5 x 4 rm	1.0	1.8	17.1	505	9	41	34	0.46	1000/D
5 x 6 re	1.0	1.8	17.7	602	9	52	44	0.69	1000/D
5 x 6 rm	1.0	1.8	18.6	650	8	52	44	0.69	1000/D
5 x 10 re	1.0	1.8	20.4	893	7	69	60	1.15	1000/D
5 x 10 rm	1.0	1.8	21.1	912	6	69	60	1.15	1000/D
5 x 16 rm	1.0	1.8	23.8	1279	5	89	80	1.84	1000/D
5 x 25 rm	1.2	1.8	28.3	1914	5	116	105	2.88	1000/D
5 x 35 rm	1.2	1.9	31.5	2505	4	138	130	4.03	1000/D
5 x 50 rm	1.4	2.0	36.4	3273	4	165	160	5.75	1000/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Control Cable

Cu/PVC/PVC 0.6/1 kV (NYY)

Specification :
SNI IEC 60502-1 : 2009



Constructions:

Conductor

Annealed plain copper solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :

- Black, with White printed number



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

- Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
- UV Resistance • Anti termite • Anti rodent • Low Smoke Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor

Packing : [D] Drum

No. of Cores and Cross Section Area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
7 x 1.5 re	0.8	1.8	14.5	324	12	17	13	0.17	1000/D
7 x 1.5 rm	0.8	1.8	15	341	11	17	13	0.17	1000/D
8 x 1.5 re	0.8	1.8	15.5	362	12	16	12	0.17	1000/D
8 x 1.5 rm	0.8	1.8	16	381	11	16	12	0.17	1000/D
10 x 1.5 re	0.8	1.8	17.4	434	12	15	12	0.17	1000/D
10 x 1.5 rm	0.8	1.8	18.1	458	11	15	12	0.17	1000/D
12 x 1.5 re	0.8	1.8	17.9	480	12	14	11	0.17	1000/D
12 x 1.5 rm	0.8	1.8	18.6	506	11	14	11	0.17	1000/D
14 x 1.5 re	0.8	1.8	18.7	542	12	13	11	0.17	1000/D
14 x 1.5 rm	0.8	1.8	19.5	572	11	13	11	0.17	1000/D
16 x 1.5 re	0.8	1.8	19.5	599	12	12	10	0.17	1000/D
16 x 1.5 rm	0.8	1.8	20.3	632	11	12	10	0.17	1000/D
19 x 1.5 re	0.8	1.8	20.4	670	12	12	9	0.17	1000/D
19 x 1.5 rm	0.8	1.8	21.3	707	11	12	9	0.17	1000/D
21 x 1.5 re	0.8	1.8	21.4	728	12	11	9	0.17	1000/D
21 x 1.5 rm	0.8	1.8	22.3	768	11	11	9	0.17	1000/D
24 x 1.5 re	0.8	1.8	23.4	821	12	11	8	0.17	1000/D
24 x 1.5 rm	0.8	1.8	24.4	866	11	11	8	0.17	1000/D
30 x 1.5 re	0.8	1.8	24.6	970	12	11	8	0.17	1000/D
30 x 1.5 rm	0.8	1.8	25.7	1024	11	11	8	0.17	1000/D
40 x 1.5 re	0.8	1.8	27.3	1226	12	11	8	0.17	1000/D
40 x 1.5 rm	0.8	1.8	28.5	1294	11	11	8	0.17	1000/D
52 x 1.5 re	0.8	1.9	32	1585	12	11	8	0.17	1000/D
52 x 1.5 rm	0.8	1.9	33.4	1673	11	11	8	0.17	1000/D
61 x 1.5 re	0.8	2.0	33	1815	12	11	8	0.17	1000/D
61 x 1.5 rm	0.8	2.0	34.6	1916	11	11	8	0.17	1000/D

Copper Conductor PVC Insulated and PVC Sheathed non Armoured Control Cable

Cu/PVC/PVC 0.6/1 kV (NYY)



Specification :
SNI IEC 60502-1 : 2009

Constructions:

Conductor

Annealed plain copper round solid or round circular stranded according to SNI IEC 60228

Insulation

Extruded layer of Polyvinyl Chloride (PVC) complied with SNI IEC 60502-1

Colour :

- Black, with White printed number



Inner Covering / filler

Extruded Polyvinyl Chloride (PVC), Black colour

Outer Sheath

The Outer Sheath shall be a layer of Extruded Polyvinyl Chloride (PVC) Grade ST1 to SNI IEC 60502-1. Black colour.

Applications:

Indoor and outdoor induct installation or of laying in the ground where not sustain mechanical damage.

Special Features on Request :

- Fire Resistance • Flame Retardant Cat. A/B/C • Oil Resistance
- UV Resistance • Anti termite • Anti rodent • Low Smoke Zero Halogen

Note : [re] round solid conductor
[rm] circular stranded conductor

Packing : [D] Drum

No. of Cores and Cross Section Area	Nominal Thickness		Overall Diameter (approx)	Weight of Cable (approx)	Min. Insulation DC Resistance at 20°	Current Carrying Capacity at 30°C		Short Circuit Current Capacity at 1.0 second	Standard delivery length
	Insulation	Outer Sheath				In Ground	In Air		
sq.mm	mm	mm	mm	kg/km	M.Ohm.km	A	A	kA	m
7 x 2.5 re	0.8	1.8	15.8	421	10	26	21	0.29	1000/D
7 x 2.5 rm	0.8	1.8	16.5	450	9	26	21	0.29	1000/D
8 x 2.5 re	0.8	1.8	16.9	471	10	23	18	0.29	1000/D
8 x 2.5 rm	0.8	1.8	17.7	505	9	23	18	0.29	1000/D
10 x 2.5 re	0.8	1.8	19.1	570	10	21	17	0.29	1000/D
10 x 2.5 rm	0.8	1.8	20.1	611	9	21	17	0.29	1000/D
12 x 2.5 re	0.8	1.8	19.7	637	10	20	16	0.29	1000/D
12 x 2.5 rm	0.8	1.8	20.7	682	9	20	16	0.29	1000/D
14 x 2.5 re	0.8	1.8	20.5	724	10	18	15	0.29	1000/D
14 x 2.5 rm	0.8	1.8	21.6	777	9	18	15	0.29	1000/D
16 x 2.5 re	0.8	1.8	21.5	804	10	17	14	0.29	1000/D
16 x 2.5rm	0.8	1.8	22.6	863	9	17	14	0.29	1000/D
19 x 2.5 re	0.8	1.8	22.5	907	10	17	13	0.29	1000/D
19 x 2.5 rm	0.8	1.8	23.6	974	9	17	13	0.29	1000/D
21 x 2.5 re	0.8	1.8	23.6	989	10	16	12	0.29	1000/D
21 x 2.5 rm	0.8	1.8	24.9	1062	9	16	12	0.29	1000/D
24 x 2.5 re	0.8	1.8	25.9	1118	10	15	11	0.29	1000/D
24 x 2.5 rm	0.8	1.8	27.3	1200	9	15	11	0.29	1000/D
30 x 2.5 re	0.8	1.8	27.3	1335	10	14	11	0.29	1000/D
30 x 2.5 rm	0.8	1.8	28.8	1433	9	14	11	0.29	1000/D
40 x 2.5 re	0.8	1.9	30.5	1718	10	14	11	0.29	1000/D
40 x 2.5 rm	0.8	1.9	32.3	1846	9	14	11	0.29	1000/D
52 x 2.5 re	0.8	2.0	35.8	2220	10	14	11	0.29	1000/D
52 x 2.5 rm	0.8	2.0	37.9	2384	9	14	11	0.29	1000/D
61 x 2.5 re	0.8	2.1	37	2552	10	14	11	0.29	1000/D
61 x 2.5 rm	0.8	2.1	39.1	2741	9	14	11	0.29	1000/D